

energex[®]

wall systems

energex[®]

ENERPRIME

100% PURE ACRYLIC COATING UTILIZED AS
A PRIMER FOR MASONRY AND STUCCO

E505

DESCRIPTION:

ENERPRIME is a water-based, roller or brush applied 100% pure acrylic Primer.

USES:

ENERPRIME is a weather resistant primer suitable for priming concrete, masonry, stucco, and acrylic based textured finishes.

CHARACTERISTICS:

Drying Time -Drying time of **ENERPRIME** is dependent upon the air temperature and relative humidity. Under average drying conditions (70°F, 55% R.H.), approximate drying time is 4 hours. Protect work from rain for at least 48 hours.

Accelerated Weathering (ASTM G-23)-passes 2000 hours.

SURFACE PREPARATION:

Surfaces shall clean, dry, above 45°F and free of efflorescence, grease, oil, form release agents and curing compounds. On previously painted surfaces, all loose, peeling and chalking paint must be removed and all gloss must be removed by sanding.

Association guidelines must be followed to insure proper installation of the wood based sheathings.

Job Conditions- Temperature for application of **Enerprime** must be 45°F or higher and must remain so for a minimum of 48 hours.

Mixing-No mixing is required. Water should not be added.

Job Conditions- Temperature for application of

ENERPRIME must be 45°F or higher and must remain so for a minimum of 24 hours.

Mixing- Thoroughly mix **ENERPRIME** with a Goldblatt Jiffler Mixer until a uniform workable consistency is obtained.

APPLICATION:

Apply with a brush or 1/2" nap roller. When applying by roller, apply **ENERPRIME** in multiple directions and then lightly finish in one direction to insure no lap marks remain. Initial coat must be completely dry before recoating. One coat covers most surfaces. Two coats are recommended for change of color. Wait 24 hours before applying second coat. **Clean Up-** Clean tools with water while **ENERPRIME** is still wet.

COVERAGE:

600 square feet per pail. Coverage also varies depending on substrate. Packaged in five gallon pails.

CAUTIONS AND LIMITATIONS:

- Do not use as a finish directly over **energex®** System reinforced Enermix Coat.

STORAGE:

ENERPRIME must be stored at 45°F or above in tightly sealed containers out of direct sunlight.

IMPORTANT NOTICE TO PURCHASER -The following is made in lieu of all warranties, express or implied: energex's (eifs, inc.) only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequently arising out of the use of or the inability to use the product. Before using user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith. The foregoing may not be altered except by an agreement signed by officers of seller and manufacturer.

energex[®]
wall systems

2960 Woodbridge Avenue
Edison, New Jersey 08837
Office (888) 343-7463
Fax (718) 932-6710